



QUAD INTEGRATED IEEE 802.3af-2003 PSE CONTROLLER AND POWER MANAGEMENT SYSTEM WITH UP TO 37W PER PORT CAPABILITIES

FEATURES

- **Standards support**
 - IEEE 802.3af-2003-compliant
 - IEEE 802.3af-2003 classification scheme support
 - Supports Pre-IEEE 802.3af-2003 legacy detection
- **High hardware integration**
 - Integrated switches
 - Integrated current sense functionality
 - Integrated microcontroller
 - Integrated AC and DC disconnect options
- **Extensive hardware features**
 - Up to 37W per port to support Power Over Ethernet (POE) PDs via integrated circuitry
 - Programmable current limit for both IEEE 802.3af and extended power ranges
 - Low-power dissipation eliminating heat sink in IEEE 802.3af mode
 - Broadcom serial control (BSC) interface support to the host
 - UART interface support to the host
 - Robust switch protection circuit withstands cable discharge and ESD events (CESD)
 - Autonomous, semi-autonomous, or manual modes
 - Real-time current, voltage and temperature measurements available per port
 - Cascading of multiple devices up to 64 ports support with the option of single hardware and software interface for the host
 - Includes four LED drivers reporting POE port activity
 - Integrated 3.3V buck regulator (DC:DC) to support up to 200 mA
 - Over-temperature protection
 - Operates from a single 48V supply
- **Extensive software features**
 - Self-contained power allocation software
 - Integrated 4-port power management
 - Integrated power management for all ports in cascaded version

SUMMARY OF BENEFITS

- **Highest integration that allows for**
 - Lowest total BOM count
 - Easier PCB placement and PCB area saving
 - Full functionality without external u-controller including power management
 - Eliminates the need for an external 48V to 3.3V power conversion
- **Further reduces BOM count via 3.3V DC:DC capability to be shared across multiple BCM59103 devices**
- **Enables support of higher than normal power PDs, such as emerging APs, security cameras, and PTZ cameras via enhanced 30W+ per port capability**
- **Eliminates the need for a heat sink in IEEE 802.3af mode via no-dissipation-Rsense and DC:DC to 3.3V**
- **Makes layout and design easy via simple ground/power plane**
- **Works with Broadcom POE-enabled products for easy implementation**
- **Architected with system-oriented features to allow for system-level differentiation, including:**
 - Single point of interface for host hardware and software
 - Power management across all ports in cascaded configuration
 - Programmable current limits and dynamic measurement per port
 - Rapid power-down to support multiple power supply failures
- **Supports a variety of applications:**
 - Routers and switches for Enterprise, SMB, SOHO, and commercial markets
 - Ethernet midspans
 - PSE power injectors
 - Integrated magnetics

